



RBxx90 VINTAGE PRESTIGE

FIELD OF APPLICATION

Wood, tiles, metal, glass, plastic, wall, fabric, steel and galvanised steel sheet. For indoor and outdoor use.

INFORMATION

Vintage Prestige is a ultra-matt enamel. It is a high-covering product, which strongly adheres to all kinds of surfaces. Its formula is odourless and with low VOC emissions. Vintage Prestige is a washable product. No sanding, no stripping, no primer application required. The application of two coats is recommended.

INSTRUCTIONS

Clean the surface from dirt, dust and grease by means of acetone, because these substances could avoid the adhesion of the coating. If old coatings peeled off, sand with 150-180 grit sandpaper. Spread the product on the surface. After 2 hours it is possible to apply a second coat. To decorate rusty metal surfaces, remove the rust with sandpaper or metallic brush. Apply an antirust, then apply Vintage Prestige products. RBxx90 can be diluted up to 10% for brush application and up to 15-20% for spray application.

OVERCOATING

Natural Effect Topcoat R03000.

PACKAGING

0,5 L

5 L *

*only RB1490, RB2090, RB2190



Storage
> 5°C



Painting
> 10°C



Ready to use



Brush
Sponge
Roller



Yield
8-10 m²/L



Mix it well
before use



Tack-free
2 h



Drying time
between the coats
4-6 h



Final drying time
6-8 h



Solid content
60 ± 10 %



Viscosity
14000 ± 1000 cps



Specific weight
1,2 ± 0,2 g/cm³



Gloss level
5



Watch our tutorials



RB1090
DARK CHERRY



RB1190
MILKSHAKE



RB1290
HAZELNUT



RB1390
VANILLA



RB1490
COCONUT



RB1590
MINTGREEN



RB1690
ANISEED



RB1790
JUNIPER



RB1890
TRUFFLE



RB1990
MARZIPAN



RB2090
MILK



RB2190
LICORICE



RB2290
SAGE



RB2390
PEACH



RB2490
CARAMEL





RBONTR RBOSBN VINTAGE PRESTIGE NEUTRAL AND WHITE BASE

FIELD OF APPLICATION

Wood, tiles, metal, glass, plastic, wall, fabric, steel and galvanised steel sheet. For indoor and outdoor use.

INFORMATION

Vintage Prestige neutral and white base must be pigmented to provide a high-covering effect and a strong adhesion to all kinds of surfaces (like the ready-to-be-applied colors). For coloring RBONTR e RBOSBN do not exceed the addition of 10% EY--M690 pastes. **No sanding, no stripping, no primer application required.** Vintage Prestige pigmented base is a washable product.

INSTRUCTIONS

Clean the surface from dirt, dust and grease by means of acetone, because these substances could avoid the adhesion of the coating. If old coatings peeled off, sand with 150-180 grit sandpaper. Spread the pigmented product on the surface. After 2 hours it is possible to apply a second coat. To decorate rusty metal surfaces, remove the rust with sandpaper or metallic brush. Apply an antirust, then apply Vintage Prestige pigmented base. Pigmented RBONTR e RBOSBN can be diluted up to 10% for brush application and up to 15-20% for spray application.

OVERCOATING

Natural Effect Topcoat R03000.

PACKAGING

RBONTR 0,92 kg 4,6 kg

RBOSBN 1 kg 5 kg



Storage
> 5°C



Painting
> 10°C



To be pigmented



Brush
Sponge
Roller



Yield
8-10 m²/L



Mix it well
before use



Tack-free
2 h



Drying time
between the coats
4-6 h



Final drying time
6-8 h



Solid content
RBONTR 45 ± 3 %
RBOSBN 63 ± 3 %



Viscosity
RBONTR
1,14 ± 0,03 g/cm³
RBOSBN
1,35 ± 0,03 g/c



Gloss level
5



RBONTR
NEUTRAL BASE 5 GLOSS



RBOSBN
WHITE BASE 5 GLOSS

