



RGxx80 GEL WOOD STAIN

FIELD OF APPLICATION

Beams, matchboardings, doors and windows, garden furniture, claddings, balconies, enclosures.

INFORMATION

The colours of RGxx80 range enhance the natural beauty of the wood. This product protects the wood from atmospheric agents and UV light, excepted the transparent version. RGxx80 range makes the wood water-repellent and the surface uniform. Its special high-viscosity formula allows the product to be applied, even vertically, without dripping. It does not leave the joints visible and makes the aesthetic result uniform.

INSTRUCTIONS

Raw wood. Sand the support with 150 grit sandpaper. Clean the surface from the sanding powder and apply 1-2 coats of product. Avoid accumulations during the application. **Stained/impregnated wood.** It is possible to apply RGxx80 on a wood treated with low-solid content dyes or impregnating stains. Once the surface has been cleaned, apply 1-2 coats of product. **Coated wood.** Sand with 80-150 grit sandpaper and bring the wood back to the raw condition. Clean the surface and proceed to impregnate.

OVERCOATING

Waxy Topcoat RC2030, Decogrip Solution RE20xx, Prestige range RBxxx0.

PACKAGING

0,75 L

5 L



Storage
> 5°C



Painting
> 10°C



Ready to use



Brush
Sponge



Yield
15 m²/L



Mix it well
before use



Tack-free
1 h



Drying time
between the coats
2 h



Final drying time
3 h



Solid content
15 ± 3 %



Viscosity
DIN2 50 ± 10"



Specific weight
1,05 ± 0,1 g/cm³



pH
8,5 ± 1,0



RG1080
TRANSPARENT



RG1180
TEAK



RG1280
CHESTNUT



RG1380
WALNUT



RG1480
DARK WALNUT



RG1680
WHITE

*Except for transparent and white version

