

RK10xx HI-DECK HYDRO OIL

FIELD OF APPLICATION

Outdoor floorings, platforms, decks, poolsides, garden furniture.

INFORMATION

It preserves the natural beauty of wood by slowing down wood greying caused by exposure to atmospheric agents. It contains broad-spectrum UV absorbers and free-radical scavengers to reduce the degrading effect of solar radiation. Easy to apply. It does not peel off, it is self-consuming.

INSTRUCTIONS

Raw wood. Sand the substrate with 150 grit sandpaper, remove the sanding powder and apply 2-3 coats of product.

MAINTENANCE

In case of objects, which are very exposed to the atmospheric agents, it is sufficient to apply 2-3 coats of RK10xx on the surface. If the object is not much exposed to the atmospheric agents, the maintenance operations will be less frequent.

OVERCOATING












Hi-Deck Hydro Oil RK10xx.

PACKAGING

0,75 L

2,5 L

10 L

-  Storage > 5°C
-  Painting > 10°C
-  Ready to use
-  Brush Roller
-  Yield per coat 12-20 m²/L
-  Mix it well before use
-  Drying time between the coats 2-3 h
-  Final drying time 48 h
-  Trampling 72 h
-  Solid content 16 ± 3 %
-  Viscosity DIN2 55 ± 10"
-  Specific weight 1,05 ± 0,1 g/cm³
-  pH 8,5 ± 1,0



RK1000
HONEY



RK1001
TEAK