



RO3000 NATURAL EFFECT TOPCOAT

FIELD OF APPLICATION

Furniture and complementary furnishings, inner doors, inner claddings, wood floorings.

INFORMATION

It protects and decorates the wood, preventing any change of the natural aspect of the wood. Fast acting and easy to apply, it makes the wood highly water-repellent and smooth to the touch. It is possible to apply a third coat of Natural effect topcoat to guarantee a higher protection.

INSTRUCTIONS

Raw wood. Carefully clean the surface from dirt, grease, waxes and resins. Sand with 150-180 grit sandpaper and remove the powder. Apply 2-3 coats of Natural effect topcoat RO3000, at intervals of 1-2 hours. Between the coats, sand the surface with 320-400 grit sandpaper.

Coated wood. Sand with 80-150 grit sandpaper and remove the powder. Then proceed as indicated for the raw wood.

MAINTENANCE

Slightly sand with 220-320 grit sandpaper, remove the powder and apply one coat of RO3000. On the most deteriorated parts, apply a second coat.

OVERCOATING

Natural effect topcoat RO3000.

PACKAGING

0,5 L

2,5 L



Storage
> 5°C



Painting
> 10°C



Ready to use



Brush
Cloth
Roller



Yield
12-24 m²/L



Mix it well
before use



Drying time
between the coats
1-2 h



Final drying time
5 h



Solid content
18 ± 3 %



Viscosity
DIN4 16 ± 3"



Specific weight
1,01 ± 0,1 g/cm³



pH
7,5 ± 0,5



Gloss level
5



RO3000
TRANSPARENT

