



## RX1000 EXCLUSIVE BASE

### FIELD OF APPLICATION

Exterior floors, deckings, jetties, pool sides, railings.

### INFORMATION

Priming treatment for exotic wood floorings to be coated with Exclusive 1 and 2. Also suitable for vertical surfaces. It nourishes hardwoods and filters out solar radiation.

### INSTRUCTIONS

**Raw wood.** Sand the support with 150 grit sandpaper, clean the surface from the sanding powder and apply 1-2 coats of product.

**Coated wood.** It is possible to apply RX1000 on a wood treated with low-solid content dyes or wood stains. Once the surface has been cleaned, sand with sandpaper or scotch brite. Then remove the powder and apply 1-2 coats of product. **Coated wood.** Sand with 80-150 grit sandpaper and bring the wood back to the raw condition. Clean the surface and apply 1-2 coats of product.

### OVERCOATING

Exclusive 1 RX50xx, Exclusive 2 RX20xx, Floor Prestige RB2x70.

### PACKAGING

0,75 L

5 L



Storage  
> 5°C



Painting  
> 10°C



Ready to use



Brush  
Cloth  
Roller



Yield  
12-20 m²/L



Mix it well  
before use



Drying time  
between the coats  
2-3 h



Overcoating  
> 3-4 h



Solid content  
15 ± 2 %



Specific weight  
1,01 ± 0,03 g/cm³



pH  
8,5 ± 1,0

