



RX1000 EXCLUSIVE BASE

FIELD OF APPLICATION

Exterior floors, deckings, jetties, pool sides, railings.

INFORMATION

Priming treatment for exotic wood floorings to be coated with Exclusive 1 and 2. Also suitable for vertical surfaces. It nourishes hardwoods and filters out solar radiation.

INSTRUCTIONS

Raw wood. Sand the support with 150 grit sandpaper, clean the surface from the sanding powder and apply 1-2 coats of product.

Coated wood. It is possible to apply RX1000 on a wood treated with low-solid content dyes or wood stains. Once the surface has been cleaned, sand with sandpaper or scotch brite. Then remove the powder and apply 1-2 coats of product.

Coated wood. Sand with 80-150 grit sandpaper and bring the wood back to the raw condition. Clean the surface and apply 1-2 coats of product.

OVERCOATING

Exclusive 1 RX50xx, Exclusive 2 RX20xx, Floor Prestige RB2x70.

PACKAGING

0,75 L

5 L

-  Storage > 5°C
-  Painting > 10°C
-  Ready to use
-  Brush
Cloth
Roller
-  Yield
12-20 m²/L
-  Mix it well
before use
-  Drying time
between the coats
2-3 h
-  Overcoating
> 3-4 h
-  Solid content
15 ± 2 %
-  Specific weight
1,01 ± 0,03 g/cm³
-  pH
8,5 ± 1,0

